

LANDWARE BEACH BLANKET INSTALLATION RECOMMENDATIONS

For Oil Tar and Debris Collection*



Note: The design of Landware Beach Blanket System should be determined by a qualified professional engineer who is familiar with oceanography and local conditions. The illustrations shown are provided for informational purposes and are not intended to be suggested designs. The company assumes no responsibility for Landware Beach Blanket System based upon these illustrations.

** Applications patent pending*

**SynTec, LLC. To Order - Call toll-free in the U.S.: 800-874-7437 • 410-327-1070 • Fax: 410-327-1078
4800 Pulaski Highway, Baltimore, Maryland 21224 • www.synteccorp.com**

COMPONENT MATERIALS





- 1** Place unrolled Landware Beach Blanket near beachshore area. Inspect roll for any punctures or tears that could have occurred during transport.



2 Unroll Landware Beach Blanket with fabric flat to beach sand. Cut and shape as desired. Note: Landware Beach Blanket comes in a variety of styles:

1. One-sided fabric with geonet
2. Two-sided fabric with geonet
3. Geonet with protrusions



3 Determine high-tide maximum reach of beach, and place Landware Beach Blanket at the approximate point to capture both high and low tide activity.



- 4** Be sure that the Landware Beach Blanket lays as flat as possible (TIP: Landware Beach Blanket can be also be used to clean oil soaked birds; as well as a pedestrian and transportation pad).



- 5** Cut holes on each corner of the Landware Beach Blanket ends and insert/drill self-locking anchors on each end. If preferred, sand bags or concrete weights can be used instead.



- 6** Allow the tides to carry the oil and debris to the beachshore.



- 7** Identify oil tars for easy removal and disposal. Please dispose of oil tar in accordance to all Federal guidelines. Be sure to replace the Landware Beach Blanket panels when they become soiled with oil, sea salt and debris.