


TURF REINFORCEMENT MESH FEATURING TENAX TR

TENAX Turf Reinforcement (TR) mesh provides reinforcement of grassy areas to minimize rutting. TR is perfect for applications where exposure to traffic is less frequent and the grass has time to recover between passes.

PHYSICAL CHARACTERISTICS	DATA
Product Description	Diamond Mesh Ground Protection
Polymer	HDPE
Stabilizer	U.V Stabilizer 2 year minimum
Color	Green
Packaging	Rolls secured with clear tape

DIMENSIONAL CHARACTERISTICS	ENGLISH			METRIC	
Mesh Size (MD x TD)	1 3/8 in x 1 2/8 in			35 mm x 33 mm	
Roll					
Size	6.7 ft x 100 ft		2.04 m x 30.5 m		
Weight	84.5 lbs		38 kg		
Tensile Strength (ASTM D 4595) ¹	MD	TD	MD	TD	
Breakage Strength	300 lbs/ft	300 lbs/ft	4,368 N/m	4,368 N/m	
Breakage Strain	>150%	>150%	>150%	>150%	

NOTES: MD: Machine Direction; TD: Cross Machine Direction

1. Test Method: ASTM D 4595 modified with a strain rate of 2 inch /minute

The above values are typical values. Values are subject to change without notice due to product modification and/or improvements at TENAX's discretion.

Manufactured by Tenax Corporation, 4800 E. Monument Street, Baltimore, MD 21205; represented exclusively in the Americas by Syntec, LLC